

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: LUMIERE

Report Number: P220423

Luminaire Tested: **9002-W1-FL-LED3597-F-BK-L1-UNV**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P220423
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29423)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: LUMIERE
Catalog Number: 9002-W1-FL-LED3597-F-BK-L1-UNV
Description: LUMIERE LANTERRA 9002 LED WALL LUMINAIRE, FLUSH LENS, FLOOD OPTIC, BLACK HOUSING.
Light Source: (1) 3500K CCT, 97 CRI LED
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 824.6 lumens
Efficiency: N/A
Efficacy: 82.5 lumens/watt
Spacing Criteria (0/90/45): 0.66 / 0.66 / 0.63
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct

Input Watts (W): 10
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P220423
CATALOG NUMBER: 9002-W1-FL-LED3597-F-BK-L1-UNV

Luminous Intensity Polar Plot





TEST NUMBER: P220423

CATALOG NUMBER: 9002-W1-FL-LED3597-F-BK-L1-UNV

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		99	98	97	95
2	110	105	102	99	108	104	101	98	101	98	96		98	96	94		95	93	92	90
3	105	100	96	92	103	98	95	91	96	93	90		94	91	89		91	89	87	86
4	101	95	90	86	99	94	89	86	91	88	85		90	86	84		88	85	83	82
5	97	90	85	81	96	89	84	81	87	83	80		86	82	80		84	81	79	78
6	93	86	81	77	92	85	80	77	84	79	76		82	79	76		81	78	75	74
7	90	82	77	73	88	81	76	73	80	76	73		79	75	72		78	75	72	71
8	86	78	73	70	85	78	73	70	77	72	69		76	72	69		75	71	69	68
9	83	75	70	67	82	75	70	67	74	69	66		73	69	66		72	69	66	65
10	80	72	67	64	79	72	67	64	71	67	64		70	66	63		69	66	63	62

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	829815
5°	832985
10°	773429
15°	642056
20°	447075
25°	268055
30°	141629
35°	67518
40°	31430
45°	13606
50°	6831
55°	3527
60°	2368
65°	1868
70°	2308
75°	0
80°	0
85°	0



TEST NUMBER: P220423

CATALOG NUMBER: 9002-W1-FL-LED3597-F-BK-L1-UNV

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	156.3	19.0
10°-20°	339.2	41.1
20°-30°	228.5	27.7
30°-40°	76.7	9.3
40°-50°	17.3	2.1
50°-60°	4.3	0.5
60°-70°	1.9	0.2
70°-80°	0.4	0.1
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	723.9	87.8
0°-40°	800.7	97.1
0°-60°	822.3	99.7
0°-90°	824.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	824.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1682	
5°	1682	156
15°	1257	339
25°	492	228
35°	112	77
45°	20	17
55°	4	4
65°	2	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P220423

CATALOG NUMBER: 9002-W1-FL-LED3597-F-BK-L1-UNV

CANDELA DISTRIBUTION (FULL):

0°	
0°	1681.9
1°	1676.3
2°	1673.0
3°	1677.1
4°	1681.9
5°	1681.9
6°	1675.4
7°	1655.9
8°	1624.3
9°	1585.3
10°	1543.8
11°	1497.5
12°	1447.1
13°	1390.2
14°	1326.9
15°	1257.0
16°	1179.8
17°	1100.2
18°	1016.5
19°	933.6
20°	851.5
21°	771.9
22°	695.5
23°	623.2
24°	555.8
25°	492.4
26°	433.9
27°	381.1
28°	331.5
29°	287.6
30°	248.6
32.5°	168.2
35°	112.1
37.5°	74.8
40°	48.8
42.5°	30.1
45°	19.5
47.5°	13.0
50°	8.9
52.5°	6.5
55°	4.1
57.5°	3.3
60°	2.4
62.5°	2.4
65°	1.6



TEST NUMBER: P220423

CATALOG NUMBER: 9002-W1-FL-LED3597-F-BK-L1-UNV

CANDELA DISTRIBUTION (continued):

	0°
67.5°	1.6
70°	1.6
72.5°	0.8
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)