

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: LUMIERE

Report Number: P221132

Luminaire Tested: **9002-W1-[RW, RI]-LED CR-F-BK-LC1-UNV**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P221132
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29546)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: LUMIERE
Catalog Number: 9002-W1-[RW, RI]-LEDCR-F-BK-LC1-UNV
Description: LUMIERE LANTERRA 9002 LED WALL LUMINAIRE, RECESSED LENS, FLOOD OPTIC, BLACK HOUSING.
Light Source: (1) COLOR CHAGING MODULE, SET TO 3500K CCT, 90 CRI LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 404.6 lumens
Efficiency: N/A
Efficacy: 30.0 lumens/watt
Spacing Criteria (0/90/45): 0.66 / 0.66 / 0.58
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 13.5
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P221132

CATALOG NUMBER: 9002-W1-[RW, RI]-LEDCR-F-BK-LC1-UNV

Luminous Intensity Polar Plot





TEST NUMBER: P221132

CATALOG NUMBER: 9002-W1-[RW, RI]-LEDCR-F-BK-LC1-UNV

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	113	111	109	112	111	109	107	107	105	104	103	102	101	99	99	98	96
2	111	107	104	101	109	105	103	100	102	100	98	99	98	96	97	95	94	93
3	107	102	99	96	105	101	98	95	98	96	93	96	94	92	94	92	91	89
4	104	98	94	91	102	97	93	90	95	92	89	93	90	88	91	89	87	86
5	100	94	90	87	99	93	89	86	92	88	85	90	87	85	89	86	84	83
6	97	90	86	83	96	90	86	83	88	85	82	87	84	82	86	83	81	80
7	94	87	83	80	93	87	82	80	85	82	79	84	81	79	83	81	78	77
8	91	84	80	77	90	84	80	77	83	79	76	82	78	76	81	78	76	75
9	88	81	77	74	87	81	77	74	80	76	74	79	76	74	79	76	73	72
10	86	79	74	72	85	78	74	72	78	74	71	77	74	71	76	73	71	70

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	523969
5°	519532
10°	487464
15°	420886
20°	256746
25°	90912
30°	6836
35°	3614
40°	2576
45°	2093
50°	1535
55°	860
60°	987
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P221132

CATALOG NUMBER: 9002-W1-[RW, RI]-LEDCR-F-BK-LC1-UNV

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	97.8	24.2
10°-20°	216.6	53.5
20°-30°	83.0	20.5
30°-40°	4.0	1.0
40°-50°	2.1	0.5
50°-60°	1.0	0.2
60°-70°	0.1	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	397.3	98.2
0°-40°	401.3	99.2
0°-60°	404.4	100.0
0°-90°	404.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	404.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1062	
5°	1049	98
15°	824	217
25°	167	83
35°	6	4
45°	3	2
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P221132

CATALOG NUMBER: 9002-W1-[RW, RI]-LED CR-F-BK-LC1-UNV

CANDELA DISTRIBUTION (FULL):

0°	
0°	1062
1°	1058
2°	1057
3°	1056
4°	1053
5°	1049
6°	1042
7°	1030
8°	1014
9°	994
10°	973
11°	951
12°	926
13°	898
14°	865
15°	824
16°	773
17°	713
18°	646
19°	569
20°	489
21°	415
22°	345
23°	281
24°	222
25°	167
26°	118
27°	77
28°	45
29°	24
30°	12
32.5°	7
35°	6
37.5°	5
40°	4
42.5°	3
45°	3
47.5°	2
50°	2
52.5°	1
55°	1
57.5°	1
60°	1
62.5°	0
65°	0



TEST NUMBER: P221132

CATALOG NUMBER: 9002-W1-[RW, RI]-LED CR-F-BK-LC1-UNV

CANDELA DISTRIBUTION (continued):

	0°
67.5°	0
70°	0
72.5°	0
75°	0
77.5°	0
80°	0
82.5°	0
85°	0
87.5°	0
90°	0

(END OF REPORT)