

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: LUMIERE

Report Number: P221130

Luminaire Tested: **9002-W1-[RW, RI]-LED CR-W-WT-LC1-UNV**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P221130
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P29545)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: LUMIERE
Catalog Number: 9002-W1-[RW, RI]-LEDCR-W-WT-LC1-UNV
Description: LUMIERE LANTERRA 9002 LED WALL LUMINAIRE, RECESSED LENS, WIDE FLOOD OPTIC, WHITE HOUSING.
Light Source: (1) COLOR CHAGING MODULE, SET TO 3500K CCT, 90 CRI LED
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 444.1 lumens
Efficiency: N/A
Efficacy: 31.3 lumens/watt
Spacing Criteria (0/90/45): 0.72 / 0.72 / 0.67
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct

Input Watts (W): 14.2
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P221130
CATALOG NUMBER: 9002-W1-[RW, RI]-LEDCR-W-WT-LC1-UNV

Luminous Intensity Polar Plot





TEST NUMBER: P221130

CATALOG NUMBER: 9002-W1-[RW, RI]-LEDCR-W-WT-LC1-UNV

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	110	107	104	110	107	105	103	103	101	99	100	98	96	96	95	94	92
2	107	101	97	93	104	100	96	92	96	93	90	93	91	88	91	88	86	85
3	101	94	89	85	99	93	88	84	90	86	83	88	84	82	86	83	80	79
4	96	88	83	78	94	87	82	78	85	81	77	83	79	76	81	78	75	74
5	92	83	77	73	90	82	77	73	80	76	72	79	75	71	77	74	71	69
6	88	79	73	68	86	78	72	68	76	71	68	75	71	67	74	70	67	65
7	84	75	69	64	82	74	68	64	73	68	64	71	67	64	70	66	63	62
8	80	71	65	61	79	70	65	61	69	64	61	68	64	60	67	63	60	59
9	77	68	62	58	76	67	62	58	66	61	58	65	61	57	64	60	57	56
10	74	65	59	55	73	64	59	55	63	58	55	63	58	55	62	58	55	53

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	350793
5°	350152
10°	337167
15°	296766
20°	221568
25°	136640
30°	67795
35°	21081
40°	19322
45°	20235
50°	19189
55°	19784
60°	20722
65°	19846
70°	18753
75°	20969
80°	19889
85°	16983



TEST NUMBER: P221130

CATALOG NUMBER: 9002-W1-[RW, RI]-LED CR-W-WT-LC1-UNV

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	66.6	15.0
10°-20°	157.3	35.4
20°-30°	114.4	25.8
30°-40°	32.2	7.2
40°-50°	21.9	4.9
50°-60°	20.6	4.6
60°-70°	16.6	3.7
70°-80°	11.1	2.5
80°-90°	3.4	0.8
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	338.3	76.2
0°-40°	370.5	83.4
0°-60°	413.0	93.0
0°-90°	444.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	444.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	711	
5°	707	67
15°	581	157
25°	251	114
35°	35	32
45°	29	22
55°	23	21
65°	17	17
75°	11	11
85°	3	3
90°	0	



TEST NUMBER: P221130

CATALOG NUMBER: 9002-W1-[RW, RI]-LEDCR-W-WT-LC1-UNV

CANDELA DISTRIBUTION (FULL):

0°	
0°	711
1°	709
2°	709
3°	708
4°	708
5°	707
6°	705
7°	702
8°	695
9°	685
10°	673
11°	660
12°	646
13°	628
14°	608
15°	581
16°	552
17°	521
18°	489
19°	456
20°	422
21°	386
22°	351
23°	316
24°	282
25°	251
26°	219
27°	189
28°	163
29°	140
30°	119
32.5°	70
35°	35
37.5°	32
40°	30
42.5°	30
45°	29
47.5°	27
50°	25
52.5°	24
55°	23
57.5°	22
60°	21
62.5°	19
65°	17



TEST NUMBER: P221130

CATALOG NUMBER: 9002-W1-[RW, RI]-LEDCR-W-WT-LC1-UNV

CANDELA DISTRIBUTION (continued):

	0°
67.5°	14
70°	13
72.5°	12
75°	11
77.5°	9
80°	7
82.5°	5
85°	3
87.5°	1
90°	0

(END OF REPORT)