

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: SHAPER

Report Number: P229243

Luminaire Tested: **340-6B-15-D010 / 340-EU6B-1020-9024-6LBW1LI-GFF**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P229243
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1705-068-14)
Test Lab: INNOVATION CENTER(G1)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: SHAPER
Catalog Number: 340-6B-15-D010 / 340-EU6B-1020-9024-6LBW1LI-GFF
Description: FARALLON 6" LED GLASS DOWNLIGHT. GLASS-IN-A-GLASS, FROSTED INSIDE, FROSTED OUTSIDE GLASS KIT.
Light Source: (1) 2400K CCT, 90 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 683.4 lumens
Efficiency: N/A
Efficacy: 48.5 lumens/watt
Spacing Criteria (0/90/45): 0.53 / 0.53 / 0.63
Luminous Opening: Vertical Cylinder (Dia: 0.46' x H: 0.49')
CIE Type: Direct


Input Watts (W): 14.1
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P229243

CATALOG NUMBER: 340-6B-15-D010 / 340-EU6B-1020-9024-6LBW1LI-GFF

Luminous Intensity Polar Plot





TEST NUMBER: P229243

CATALOG NUMBER: 340-6B-15-D010 / 340-EU6B-1020-9024-6LBW1LI-GFF

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	118	118	118	118	115	115	115	115	109	109	109	104	104	104	99	99	99	96
1	107	102	97	93	104	99	95	91	94	91	88	90	87	84	85	83	81	79
2	98	89	82	77	95	87	81	75	83	78	73	79	75	71	76	72	69	66
3	90	79	71	65	87	77	70	64	74	68	62	71	65	61	68	63	59	57
4	83	71	63	56	80	70	62	56	67	60	54	64	58	53	61	56	52	50
5	77	65	56	49	75	63	55	49	61	54	48	58	52	47	56	51	47	44
6	72	59	50	44	70	58	50	44	56	49	43	54	47	43	52	46	42	40
7	67	54	46	40	65	53	45	40	51	44	39	50	43	39	48	43	38	36
8	63	50	42	37	61	49	42	36	48	41	36	46	40	36	45	39	35	33
9	60	47	39	34	58	46	39	34	45	38	33	43	37	33	42	37	33	31
10	56	44	36	31	55	43	36	31	42	35	31	41	35	31	40	34	30	29

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	38525
5°	34167
10°	28474
15°	15935
20°	10649
25°	8228
30°	6650
35°	5544
40°	4944
45°	4531
50°	4136
55°	3707
60°	3309
65°	2861
70°	2452
75°	2074
80°	1764
85°	1470



TEST NUMBER: P229243

CATALOG NUMBER: 340-6B-15-D010 / 340-EU6B-1020-9024-6LBW1LI-GFF

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	54.3	7.9
10°-20°	94.5	13.8
20°-30°	86.7	12.7
30°-40°	86.2	12.6
40°-50°	89.5	13.1
50°-60°	86.0	12.6
60°-70°	72.0	10.5
70°-80°	53.1	7.8
80°-90°	35.9	5.3
90°-100°	20.8	3.1
100°-110°	4.3	0.6
110°-120°	0.1	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	235.5	34.5
0°-40°	321.6	47.1
0°-60°	497.2	72.7
0°-90°	658.2	96.3
90°-120°	25.3	3.7
90°-150°	25.3	3.7
90°-180°	25.0	3.7
0°-180°	683.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	590	
5°	584	54
15°	322	95
25°	187	87
35°	136	86
45°	116	90
55°	96	86
65°	73	72
75°	50	53
85°	32	28
90°	26	14
95°	20	14
105°	3	4
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0



TEST NUMBER: P229243

CATALOG NUMBER: 340-6B-15-D010 / 340-EU6B-1020-9024-6LBW1LI-GFF

CANDELA DISTRIBUTION (FULL):

0°	
0°	590.5
2.5°	589.6
5°	583.8
7.5°	570.5
10°	532.9
12.5°	430.3
15°	321.9
17.5°	264.4
20°	229.3
22.5°	205.2
25°	186.8
27.5°	171.8
30°	157.6
32.5°	145.1
35°	135.9
37.5°	129.3
40°	124.3
42.5°	120.1
45°	115.9
47.5°	111.8
50°	106.8
52.5°	101.7
55°	95.9
57.5°	90.9
60°	85.1
62.5°	78.4
65°	72.6
67.5°	66.7
70°	60.9
72.5°	55.0
75°	50.0
77.5°	45.0
80°	40.9
82.5°	36.7
85°	32.5
87.5°	29.2
90°	25.9
92.5°	23.4
95°	20.0
97.5°	15.0
100°	10.0
102.5°	5.8
105°	3.3
107.5°	1.7
110°	0.8



TEST NUMBER: P229243

CATALOG NUMBER: 340-6B-15-D010 / 340-EU6B-1020-9024-6LBW1LI-GFF

CANDELA DISTRIBUTION (continued):

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)