

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: SHAPER

Report Number: P229276

Luminaire Tested: **340-6B-15-D010 / 340-EU6B-1020-9050-6LBW1LI-GFC**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P229276
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1705-068-15)
Test Lab: INNOVATION CENTER(G1)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: SHAPER
Catalog Number: 340-6B-15-D010 / 340-EU6B-1020-9050-6LBW1LI-GFC
Description: FARALLON 6" LED GLASS DOWNLIGHT. GLASS-IN-A-GLASS, FROSTED INSIDE, CLEAR OUTSIDE GLASS KIT.
Light Source: (1) 5000K CCT, 90 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 884.4 lumens
Efficiency: N/A
Efficacy: 62.7 lumens/watt
Spacing Criteria (0/90/45): 0.61 / 0.61 / 0.74
Luminous Opening: Vertical Cylinder (Dia: 0.46' x H: 0.49')
CIE Type: Direct


Input Watts (W): 14.1
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P229276

CATALOG NUMBER: 340-6B-15-D010 / 340-EU6B-1020-9050-6LBW1LI-GFC

Luminous Intensity Polar Plot





TEST NUMBER: P229276

CATALOG NUMBER: 340-6B-15-D010 / 340-EU6B-1020-9050-6LBW1LI-GFC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	110	110	110		105	105	105		100	100	100	98
1	109	105	101	97	106	102	99	96	98	95	92		94	91	89		90	88	86	84
2	101	93	87	82	98	91	86	81	88	83	79		84	80	77		81	78	75	73
3	93	84	76	71	91	82	75	70	79	73	69		76	71	67		73	69	66	64
4	86	76	68	62	84	74	67	61	72	65	60		69	64	60		67	62	59	57
5	81	69	61	55	78	68	60	55	66	59	54		64	58	53		62	57	53	51
6	75	63	55	50	73	62	55	49	60	54	49		59	53	48		57	52	48	46
7	71	58	51	45	69	58	50	45	56	49	44		54	49	44		53	48	44	42
8	66	54	47	41	65	54	46	41	52	46	41		51	45	41		50	44	40	38
9	63	51	43	38	61	50	43	38	49	42	38		48	42	37		47	41	37	36
10	59	47	40	35	58	47	40	35	46	39	35		45	39	35		44	38	35	33

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	49935
5°	44854
10°	38696
15°	24395
20°	17424
25°	13378
30°	10782
35°	9069
40°	8003
45°	6841
50°	5491
55°	4276
60°	3363
65°	2657
70°	2146
75°	1709
80°	1388
85°	1090



TEST NUMBER: P229276

CATALOG NUMBER: 340-6B-15-D010 / 340-EU6B-1020-9050-6LBW1LI-GFC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	72.1	8.1
10°-20°	142.2	16.1
20°-30°	140.9	15.9
30°-40°	140.4	15.9
40°-50°	134.0	15.2
50°-60°	100.0	11.3
60°-70°	67.8	7.7
70°-80°	44.2	5.0
80°-90°	26.9	3.0
90°-100°	14.0	1.6
100°-110°	1.9	0.2
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	355.2	40.2
0°-40°	495.6	56.0
0°-60°	729.7	82.5
0°-90°	868.5	98.2
90°-120°	15.9	1.8
90°-150°	15.9	1.8
90°-180°	16.0	1.8
0°-180°	884.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	765	
5°	766	72
15°	493	142
25°	304	141
35°	222	140
45°	175	134
55°	111	100
65°	67	68
75°	41	44
85°	24	21
90°	18	10
95°	13	9
105°	1	2
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0



TEST NUMBER: P229276

CATALOG NUMBER: 340-6B-15-D010 / 340-EU6B-1020-9050-6LBW1LI-GFC

CANDELA DISTRIBUTION (FULL):

0°	
0°	765.4
2.5°	766.4
5°	766.4
7.5°	760.4
10°	724.2
12.5°	612.5
15°	492.8
17.5°	425.4
20°	375.2
22.5°	334.9
25°	303.7
27.5°	277.6
30°	255.5
32.5°	236.4
35°	222.3
37.5°	211.2
40°	201.2
42.5°	190.1
45°	175.0
47.5°	158.9
50°	141.8
52.5°	125.7
55°	110.6
57.5°	97.6
60°	86.5
62.5°	76.4
65°	67.4
67.5°	60.3
70°	53.3
72.5°	47.3
75°	41.2
77.5°	36.2
80°	32.2
82.5°	28.2
85°	24.1
87.5°	21.1
90°	18.1
92.5°	16.1
95°	13.1
97.5°	10.1
100°	6.0
102.5°	3.0
105°	1.0
107.5°	0.0
110°	0.0



TEST NUMBER: P229276

CATALOG NUMBER: 340-6B-15-D010 / 340-EU6B-1020-9050-6LBW1LI-GFC

CANDELA DISTRIBUTION (continued):

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)