

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: SHAPER

Report Number: P229161

Luminaire Tested: **340-6B-20-D010 / 340-EU6B-1020-9024-6LBW1LI-CC**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P229161
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1705-068-11)
Test Lab: INNOVATION CENTER(G1)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: SHAPER
Catalog Number: 340-6B-20-D010 / 340-EU6B-1020-9024-6LBW1LI-CC
Description: FARALLON 6" LED GLASS DOWNLIGHT. CYLINDRICAL CLEAR GLASS KIT.
Light Source: (1) 2400K CCT, 90 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1063.6 lumens
Efficiency: N/A
Efficacy: 51.1 lumens/watt
Spacing Criteria (0/90/45): 0.44 / 0.44 / 0.71
Luminous Opening: Circular (Dia: 0.46' x H: 0')
CIE Type: Direct


Input Watts (W): 20.8
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P229161

CATALOG NUMBER: 340-6B-20-D010 / 340-EU6B-1020-9024-6LBW1LI-CC

Luminous Intensity Polar Plot





TEST NUMBER: P229161

CATALOG NUMBER: 340-6B-20-D010 / 340-EU6B-1020-9024-6LBW1LI-CC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97	96	94	93
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91	89	87	85
3	101	95	89	85	99	93	88	84	90	86	83		88	85	82		86	83	80	79
4	96	88	82	78	94	87	81	77	85	80	76		83	79	75		81	77	74	73
5	91	82	76	71	89	81	75	71	79	74	70		78	73	70		76	72	69	68
6	86	77	71	66	85	76	70	66	74	69	65		73	68	65		72	68	64	63
7	82	72	66	61	80	71	65	61	70	65	61		69	64	61		68	63	60	59
8	78	68	62	57	76	67	61	57	66	61	57		65	60	57		64	60	56	55
9	74	64	58	54	73	63	58	54	62	57	53		62	57	53		61	56	53	52
10	70	60	54	50	69	60	54	50	59	54	50		58	53	50		58	53	50	49

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	120793
5°	98628
10°	72276
15°	62409
20°	53445
25°	49411
30°	39829
35°	25852
40°	19554
45°	10915
50°	6354
55°	4220
60°	2871
65°	1791
70°	1545
75°	1160
80°	864
85°	898



TEST NUMBER: P229161

CATALOG NUMBER: 340-6B-20-D010 / 340-EU6B-1020-9024-6LBW1LI-CC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	130.2	12.2
10°-20°	258.6	24.3
20°-30°	305.7	28.7
30°-40°	213.9	20.1
40°-50°	99.8	9.4
50°-60°	34.6	3.3
60°-70°	13.1	1.2
70°-80°	5.3	0.5
80°-90°	1.3	0.1
90°-100°	0.8	0.1
100°-110°	0.5	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	694.5	65.3
0°-40°	908.4	85.4
0°-60°	1042.8	98.0
0°-90°	1062.6	99.9
90°-120°	1.3	0.1
90°-150°	1.3	0.1
90°-180°	1.0	0.1
0°-180°	1063.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1852	
5°	1506	130
15°	924	259
25°	686	306
35°	325	214
45°	118	100
55°	37	35
65°	12	13
75°	5	5
85°	1	1
90°	0	0
95°	0	0
105°	0	0
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0



TEST NUMBER: P229161

CATALOG NUMBER: 340-6B-20-D010 / 340-EU6B-1020-9024-6LBW1LI-CC

CANDELA DISTRIBUTION (FULL):

0°	
0°	1851.5
2.5°	1759.9
5°	1506.0
7.5°	1255.6
10°	1091.0
12.5°	993.6
15°	924.0
17.5°	861.4
20°	769.8
22.5°	701.4
25°	686.4
27.5°	628.4
30°	528.7
32.5°	416.2
35°	324.6
37.5°	265.5
40°	229.6
42.5°	178.5
45°	118.3
47.5°	82.3
50°	62.6
52.5°	47.5
55°	37.1
57.5°	29.0
60°	22.0
62.5°	16.2
65°	11.6
67.5°	10.4
70°	8.1
72.5°	7.0
75°	4.6
77.5°	3.5
80°	2.3
82.5°	1.2
85°	1.2
87.5°	1.2
90°	0.0
92.5°	0.0
95°	0.0
97.5°	1.2
100°	1.2
102.5°	1.2
105°	0.0
107.5°	0.0
110°	0.0



TEST NUMBER: P229161

CATALOG NUMBER: 340-6B-20-D010 / 340-EU6B-1020-9024-6LBW1LI-CC

CANDELA DISTRIBUTION (continued):

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)