

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: SHAPER

Report Number: P229166

Luminaire Tested: **340-6B-20-D010 / 340-EU6B-1020-9050-6LBW1LI-CC**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P229166
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1705-068-11)
Test Lab: INNOVATION CENTER(G1)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: SHAPER
Catalog Number: 340-6B-20-D010 / 340-EU6B-1020-9050-6LBW1LI-CC
Description: FARALLON 6" LED GLASS DOWNLIGHT. CYLINDRICAL CLEAR GLASS KIT.
Light Source: (1) 5000K CCT, 90 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1282.6 lumens
Efficiency: N/A
Efficacy: 61.7 lumens/watt
Spacing Criteria (0/90/45): 0.44 / 0.44 / 0.71
Luminous Opening: Circular (Dia: 0.46' x H: 0')
CIE Type: Direct


Input Watts (W): 20.8
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P229166

CATALOG NUMBER: 340-6B-20-D010 / 340-EU6B-1020-9050-6LBW1LI-CC

Luminous Intensity Polar Plot





TEST NUMBER: P229166

CATALOG NUMBER: 340-6B-20-D010 / 340-EU6B-1020-9050-6LBW1LI-CC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	94	93
2	107	102	98	94	105	100	96	93	97	94	91	94	91	89	91	89	87	85
3	101	95	89	85	99	93	88	84	90	86	83	88	85	82	86	83	80	79
4	96	88	82	78	94	87	81	77	85	80	76	83	79	75	81	77	74	73
5	91	82	76	71	89	81	75	71	79	74	70	78	73	70	76	72	69	68
6	86	77	71	66	85	76	70	66	74	69	65	73	68	65	72	68	64	63
7	82	72	66	61	80	71	65	61	70	65	61	69	64	61	68	63	60	59
8	78	68	62	57	76	67	61	57	66	61	57	65	60	57	64	60	56	55
9	74	64	58	54	73	63	58	54	62	57	53	62	57	53	61	56	53	52
10	70	60	54	50	69	60	54	50	59	54	50	58	53	50	58	53	50	49

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	145682
5°	118949
10°	87161
15°	75269
20°	64457
25°	59582
30°	48033
35°	31181
40°	23574
45°	13157
50°	7663
55°	5084
60°	3471
65°	2161
70°	1869
75°	1412
80°	1052
85°	1048



TEST NUMBER: P229166

CATALOG NUMBER: 340-6B-20-D010 / 340-EU6B-1020-9050-6LBW1LI-CC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	157.0	12.2
10°-20°	311.8	24.3
20°-30°	368.6	28.7
30°-40°	258.0	20.1
40°-50°	120.4	9.4
50°-60°	41.8	3.3
60°-70°	15.9	1.2
70°-80°	6.5	0.5
80°-90°	1.5	0.1
90°-100°	1.0	0.1
100°-110°	0.6	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	837.5	65.3
0°-40°	1095.5	85.4
0°-60°	1257.6	98.1
0°-90°	1281.5	99.9
90°-120°	1.5	0.1
90°-150°	1.5	0.1
90°-180°	2.0	0.2
0°-180°	1282.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2233	
5°	1816	157
15°	1114	312
25°	828	369
35°	392	258
45°	143	120
55°	45	42
65°	14	16
75°	6	6
85°	1	1
90°	0	0
95°	0	1
105°	0	1
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0



TEST NUMBER: P229166

CATALOG NUMBER: 340-6B-20-D010 / 340-EU6B-1020-9050-6LBW1LI-CC

CANDELA DISTRIBUTION (FULL):

0°	
0°	2233.0
2.5°	2122.5
5°	1816.3
7.5°	1514.3
10°	1315.7
12.5°	1198.3
15°	1114.4
17.5°	1038.9
20°	928.4
22.5°	845.9
25°	827.7
27.5°	757.8
30°	637.6
32.5°	502.0
35°	391.5
37.5°	320.2
40°	276.8
42.5°	215.3
45°	142.6
47.5°	99.3
50°	75.5
52.5°	57.3
55°	44.7
57.5°	35.0
60°	26.6
62.5°	19.6
65°	14.0
67.5°	12.6
70°	9.8
72.5°	8.4
75°	5.6
77.5°	4.2
80°	2.8
82.5°	1.4
85°	1.4
87.5°	1.4
90°	0.0
92.5°	0.0
95°	0.0
97.5°	1.4
100°	1.4
102.5°	1.4
105°	0.0
107.5°	0.0
110°	0.0



TEST NUMBER: P229166

CATALOG NUMBER: 340-6B-20-D010 / 340-EU6B-1020-9050-6LBW1LI-CC

CANDELA DISTRIBUTION (continued):

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)