

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: SHAPER

Report Number: P229169

Luminaire Tested: **340-6B-30-D010 / 340-EU6B-3040-9030-6LBW1LI-CC**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P229169  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1705-068-11)  
Test Lab: INNOVATION CENTER(G1)  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: SHAPER  
Catalog Number: 340-6B-30-D010 / 340-EU6B-3040-9030-6LBW1LI-CC  
Description: FARALLON 6" LED GLASS DOWNLIGHT. CYLINDRICAL CLEAR GLASS KIT.  
Light Source: (1) 3000K CCT, 90 CRI LEDS  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1822.7 lumens  
Efficiency: N/A  
Efficacy: 65.1 lumens/watt  
Spacing Criteria (0/90/45): 0.44 / 0.44 / 0.71  
Luminous Opening: Circular (Dia: 0.46' x H: 0')  
CIE Type: Direct


Input Watts (W): 28  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P229169

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9030-6LBW1LI-CC

### Luminous Intensity Polar Plot





TEST NUMBER: P229169

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9030-6LBW1LI-CC

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97	96	94	93
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91	89	87	85
3	101	95	89	85	99	93	88	84	90	86	83		88	85	82		86	83	80	79
4	96	88	82	78	94	87	81	77	85	80	76		83	79	75		81	77	74	73
5	91	82	76	71	89	81	75	71	79	74	70		78	73	70		76	72	69	68
6	86	77	71	66	85	76	70	66	74	69	65		73	68	65		72	68	64	63
7	82	72	66	61	80	71	65	61	70	65	61		69	64	61		68	63	60	59
8	78	68	62	57	76	67	61	57	66	61	57		65	60	57		64	60	56	55
9	74	64	58	54	73	63	58	54	62	57	53		62	57	53		61	56	53	52
10	70	60	54	50	69	60	54	50	59	54	50		58	53	50		58	53	50	49

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	207015
5°	169029
10°	123862
15°	106960
20°	91596
25°	84676
30°	68252
35°	44306
40°	33504
45°	18702
50°	10891
55°	7234
60°	4932
65°	3072
70°	2651
75°	1991
80°	1503
85°	1497



TEST NUMBER: P229169

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9030-6LBW1LI-CC

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	223.2	12.2
10°-20°	443.1	24.3
20°-30°	523.9	28.7
30°-40°	366.6	20.1
40°-50°	171.1	9.4
50°-60°	59.4	3.3
60°-70°	22.6	1.2
70°-80°	9.1	0.5
80°-90°	2.2	0.1
90°-100°	1.4	0.1
100°-110°	0.8	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1190.2	65.3
0°-40°	1556.7	85.4
0°-60°	1787.2	98.1
0°-90°	1821.1	99.9
90°-120°	2.2	0.1
90°-150°	2.2	0.1
90°-180°	2.0	0.1
0°-180°	1822.7	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	3173	
5°	2581	223
15°	1584	443
25°	1176	524
35°	556	367
45°	203	171
55°	64	59
65°	20	23
75°	8	9
85°	2	2
90°	0	0
95°	0	1
105°	0	1
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0



TEST NUMBER: P229169

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9030-6LBW1LI-CC

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	3173.1
2.5°	3016.1
5°	2581.0
7.5°	2151.8
10°	1869.7
12.5°	1702.8
15°	1583.6
17.5°	1476.3
20°	1319.3
22.5°	1202.1
25°	1176.3
27.5°	1076.9
30°	906.0
32.5°	713.3
35°	556.3
37.5°	455.0
40°	393.4
42.5°	306.0
45°	202.7
47.5°	141.1
50°	107.3
52.5°	81.5
55°	63.6
57.5°	49.7
60°	37.8
62.5°	27.8
65°	19.9
67.5°	17.9
70°	13.9
72.5°	11.9
75°	7.9
77.5°	6.0
80°	4.0
82.5°	2.0
85°	2.0
87.5°	2.0
90°	0.0
92.5°	0.0
95°	0.0
97.5°	2.0
100°	2.0
102.5°	2.0
105°	0.0
107.5°	0.0
110°	0.0



TEST NUMBER: P229169

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9030-6LBW1LI-CC

**CANDELA DISTRIBUTION (continued):**

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)