

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: SHAPER

Report Number: P229172

Luminaire Tested: **340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-CC**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P229172  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1705-068-11)  
Test Lab: INNOVATION CENTER(G1)  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: SHAPER  
Catalog Number: 340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-CC  
Description: FARALLON 6" LED GLASS DOWNLIGHT. CYLINDRICAL CLEAR GLASS KIT.  
Light Source: (1) 5000K CCT, 90 CRI LEDS  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1859.5 lumens  
Efficiency: N/A  
Efficacy: 66.4 lumens/watt  
Spacing Criteria (0/90/45): 0.44 / 0.44 / 0.71  
Luminous Opening: Circular (Dia: 0.46' x H: 0')  
CIE Type: Direct


Input Watts (W): 28  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P229172

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-CC

### Luminous Intensity Polar Plot





TEST NUMBER: P229172

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-CC

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	110	108	105	111	108	106	104	104	102	100	100	99	97	97	96	94	93
2	107	102	98	94	105	100	96	93	97	94	91	94	91	89	91	89	87	85
3	101	95	89	85	99	93	88	84	90	86	83	88	85	82	86	83	80	79
4	96	88	82	78	94	87	81	77	85	80	76	83	79	75	81	77	74	73
5	91	82	76	71	89	81	75	71	79	74	70	78	73	70	76	72	69	68
6	86	77	71	66	85	76	70	66	74	69	65	73	68	65	72	68	64	63
7	82	72	66	61	80	71	65	61	70	65	61	69	64	61	68	63	60	59
8	78	68	62	57	76	67	61	57	66	61	57	65	60	57	64	60	56	55
9	74	64	58	54	73	63	58	54	62	57	53	62	57	53	61	56	53	52
10	70	60	54	50	69	60	54	50	59	54	50	58	53	50	58	53	50	49

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	211203
5°	172454
10°	126366
15°	109121
20°	93450
25°	86389
30°	69638
35°	45206
40°	34185
45°	19080
50°	11114
55°	7382
60°	5024
65°	3134
70°	2709
75°	2042
80°	1540
85°	1497



TEST NUMBER: P229172

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-CC

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	227.7	12.2
10°-20°	452.1	24.3
20°-30°	534.5	28.7
30°-40°	374.0	20.1
40°-50°	174.5	9.4
50°-60°	60.6	3.3
60°-70°	23.0	1.2
70°-80°	9.4	0.5
80°-90°	2.2	0.1
90°-100°	1.4	0.1
100°-110°	0.8	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1214.3	65.3
0°-40°	1588.3	85.4
0°-60°	1823.4	98.1
0°-90°	1857.9	99.9
90°-120°	2.2	0.1
90°-150°	2.2	0.1
90°-180°	2.0	0.1
0°-180°	1859.5	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	3237	
5°	2633	228
15°	1616	452
25°	1200	534
35°	568	374
45°	207	175
55°	65	61
65°	20	23
75°	8	9
85°	2	2
90°	0	0
95°	0	1
105°	0	1
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0



TEST NUMBER: P229172

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-CC

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	3237.3
2.5°	3077.2
5°	2633.3
7.5°	2195.4
10°	1907.5
12.5°	1737.3
15°	1615.6
17.5°	1506.2
20°	1346.0
22.5°	1226.4
25°	1200.1
27.5°	1098.7
30°	924.4
32.5°	727.7
35°	567.6
37.5°	464.2
40°	401.4
42.5°	312.2
45°	206.8
47.5°	143.9
50°	109.5
52.5°	83.1
55°	64.9
57.5°	50.7
60°	38.5
62.5°	28.4
65°	20.3
67.5°	18.2
70°	14.2
72.5°	12.2
75°	8.1
77.5°	6.1
80°	4.1
82.5°	2.0
85°	2.0
87.5°	2.0
90°	0.0
92.5°	0.0
95°	0.0
97.5°	2.0
100°	2.0
102.5°	2.0
105°	0.0
107.5°	0.0
110°	0.0



TEST NUMBER: P229172

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-CC

**CANDELA DISTRIBUTION (continued):**

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)