

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: SHAPER

Report Number: P229230

Luminaire Tested: **340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-CQ**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P229230  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1705-068-13)  
Test Lab: INNOVATION CENTER(G1)  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: SHAPER  
Catalog Number: 340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-CQ  
Description: FARALLON 6" LED GLASS DOWNLIGHT CYLINDRICAL FROSTED, QUADRATE ETCHED GLASS KIT.  
Light Source: (1) 5000K CCT, 90 CRI LEDS  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1736.4 lumens  
Efficiency: N/A  
Efficacy: 62.0 lumens/watt  
Spacing Criteria (0/90/45): 0.4 / 0.4 / 0.54  
Luminous Opening: Vertical Cylinder (Dia: 0.46' x H: 0.49')  
CIE Type: Direct


Input Watts (W): 28  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P229230

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-CQ

### Luminous Intensity Polar Plot





TEST NUMBER: P229230

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-CQ

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	110	110	110	105	105	105	100	100	100	98
1	110	105	102	98	107	103	100	97	98	96	93	94	92	90	90	89	87	85
2	102	95	89	84	99	93	87	83	89	84	81	85	82	78	82	79	76	74
3	95	86	79	73	92	84	78	72	81	75	71	78	73	70	75	71	68	66
4	88	78	71	65	86	77	70	64	74	68	63	72	67	62	69	65	61	59
5	83	72	64	58	81	71	63	58	68	62	57	66	61	57	64	60	56	54
6	78	66	59	53	76	65	58	53	63	57	52	62	56	52	60	55	51	49
7	73	62	54	49	71	61	54	49	59	53	48	58	52	48	56	51	47	46
8	69	58	50	45	68	57	50	45	55	49	45	54	48	44	53	48	44	42
9	66	54	47	42	64	53	47	42	52	46	42	51	45	41	50	45	41	40
10	62	51	44	40	61	50	44	39	49	43	39	48	43	39	47	42	39	37

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	173253
5°	124455
10°	78963
15°	63219
20°	43490
25°	24108
30°	18905
35°	15877
40°	13949
45°	11572
50°	9500
55°	7523
60°	5992
65°	4714
70°	3753
75°	3029
80°	2449
85°	2018



TEST NUMBER: P229230

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-CQ

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	181.7	10.5
10°-20°	348.8	20.1
20°-30°	270.7	15.6
30°-40°	246.3	14.2
40°-50°	228.5	13.2
50°-60°	175.9	10.1
60°-70°	120.3	6.9
70°-80°	78.1	4.5
80°-90°	48.6	2.8
90°-100°	28.2	1.6
100°-110°	8.9	0.5
110°-120°	0.3	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	801.2	46.1
0°-40°	1047.5	60.3
0°-60°	1451.9	83.6
0°-90°	1699.0	97.8
90°-120°	37.4	2.2
90°-150°	37.4	2.2
90°-180°	37.0	2.1
0°-180°	1736.4	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	2656	
5°	2126	182
15°	1277	349
25°	547	271
35°	389	246
45°	296	228
55°	195	176
65°	120	120
75°	73	78
85°	45	39
90°	32	18
95°	26	20
105°	8	9
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0



TEST NUMBER: P229230

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-CQ

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	2655.6
2.5°	2538.0
5°	2126.5
7.5°	1729.2
10°	1477.8
12.5°	1354.1
15°	1277.1
17.5°	1177.8
20°	936.5
22.5°	654.8
25°	547.3
27.5°	494.6
30°	448.0
32.5°	411.5
35°	389.2
37.5°	375.0
40°	350.7
42.5°	322.3
45°	296.0
47.5°	269.6
50°	245.3
52.5°	218.9
55°	194.6
57.5°	174.3
60°	154.1
62.5°	135.8
65°	119.6
67.5°	107.4
70°	93.2
72.5°	83.1
75°	73.0
77.5°	64.9
80°	56.8
82.5°	50.7
85°	44.6
87.5°	38.5
90°	32.4
92.5°	30.4
95°	26.4
97.5°	22.3
100°	16.2
102.5°	12.2
105°	8.1
107.5°	4.1
110°	2.0



TEST NUMBER: P229230

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-CQ

**CANDELA DISTRIBUTION (continued):**

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)