

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: SHAPER

Report Number: P229288

Luminaire Tested: **340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-GFC**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P229288  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1705-068-15)  
Test Lab: INNOVATION CENTER(G1)  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: SHAPER  
Catalog Number: 340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-GFC  
Description: FARALLON 6" LED GLASS DOWNLIGHT. GLASS-IN-A-GLASS, FROSTED INSIDE, CLEAR OUTSIDE GLASS KIT.  
Light Source: (1) 5000K CCT, 90 CRI LEDS  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1782.6 lumens  
Efficiency: N/A  
Efficacy: 63.7 lumens/watt  
Spacing Criteria (0/90/45): 0.61 / 0.61 / 0.74  
Luminous Opening: Vertical Cylinder (Dia: 0.46' x H: 0.49')  
CIE Type: Direct


Input Watts (W): 28  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P229288

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-GFC

### Luminous Intensity Polar Plot





TEST NUMBER: P229288

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-GFC

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	110	110	110		105	105	105		100	100	100	98
1	109	105	101	97	106	102	99	96	98	95	92		94	91	89		90	88	86	84
2	101	93	87	82	98	91	86	81	88	83	79		84	80	77		81	78	75	73
3	93	84	76	71	91	82	75	70	79	73	69		76	71	67		73	69	66	64
4	86	76	68	62	84	74	67	61	72	65	60		69	64	60		67	62	59	57
5	81	69	61	55	78	68	60	55	66	59	54		64	58	53		62	57	53	51
6	75	63	55	50	73	62	55	49	60	54	49		59	53	48		57	52	48	46
7	71	58	51	45	69	58	50	45	56	49	44		54	49	44		53	48	44	42
8	66	54	47	41	65	54	46	41	52	46	41		51	45	41		50	44	40	38
9	63	51	43	38	61	50	43	38	49	42	38		48	42	37		47	41	37	36
10	59	47	40	35	58	47	40	35	46	39	35		45	39	35		44	38	35	33

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	100647
5°	90405
10°	77986
15°	49171
20°	35113
25°	26967
30°	21728
35°	18276
40°	16125
45°	13789
50°	11068
55°	8621
60°	6777
65°	5352
70°	4325
75°	3448
80°	2798
85°	2203



TEST NUMBER: P229288

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-GFC

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	145.2	8.1
10°-20°	286.7	16.1
20°-30°	284.0	15.9
30°-40°	283.0	15.9
40°-50°	270.1	15.2
50°-60°	201.6	11.3
60°-70°	136.6	7.7
70°-80°	89.1	5.0
80°-90°	54.2	3.0
90°-100°	28.2	1.6
100°-110°	3.8	0.2
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	715.9	40.2
0°-40°	998.9	56.0
0°-60°	1470.6	82.5
0°-90°	1750.6	98.2
90°-120°	32.1	1.8
90°-150°	32.1	1.8
90°-180°	32.0	1.8
0°-180°	1782.6	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1543	
5°	1545	145
15°	993	287
25°	612	284
35°	448	283
45°	353	270
55°	223	202
65°	136	137
75°	83	89
85°	49	43
90°	36	20
95°	26	19
105°	2	4
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0



TEST NUMBER: P229288

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-GFC

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	1542.7
2.5°	1544.7
5°	1544.7
7.5°	1532.5
10°	1459.5
12.5°	1234.5
15°	993.3
17.5°	857.5
20°	756.1
22.5°	675.0
25°	612.2
27.5°	559.5
30°	514.9
32.5°	476.4
35°	448.0
37.5°	425.7
40°	405.4
42.5°	383.1
45°	352.7
47.5°	320.3
50°	285.8
52.5°	253.4
55°	223.0
57.5°	196.6
60°	174.3
62.5°	154.1
65°	135.8
67.5°	121.6
70°	107.4
72.5°	95.3
75°	83.1
77.5°	73.0
80°	64.9
82.5°	56.8
85°	48.7
87.5°	42.6
90°	36.5
92.5°	32.4
95°	26.4
97.5°	20.3
100°	12.2
102.5°	6.1
105°	2.0
107.5°	0.0
110°	0.0



TEST NUMBER: P229288

CATALOG NUMBER: 340-6B-30-D010 / 340-EU6B-3040-9050-6LBW1LI-GFC

**CANDELA DISTRIBUTION (continued):**

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)