

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: SHAPER

Report Number: P229177

Luminaire Tested: **340-6B-40-D010 / 340-EU6B-3040-9040-6LBW1LI-CC**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P229177
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1705-068-11)
Test Lab: INNOVATION CENTER(G1)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: SHAPER
Catalog Number: 340-6B-40-D010 / 340-EU6B-3040-9040-6LBW1LI-CC
Description: FARALLON 6" LED GLASS DOWNLIGHT. CYLINDRICAL CLEAR GLASS KIT.
Light Source: (1) 4000K CCT, 90 CRI LEDS
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2617.8 lumens
Efficiency: N/A
Efficacy: 62.6 lumens/watt
Spacing Criteria (0/90/45): 0.44 / 0.44 / 0.71
Luminous Opening: Circular (Dia: 0.46' x H: 0')
CIE Type: Direct


Input Watts (W): 41.8
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P229177

CATALOG NUMBER: 340-6B-40-D010 / 340-EU6B-3040-9040-6LBW1LI-CC

Luminous Intensity Polar Plot





TEST NUMBER: P229177

CATALOG NUMBER: 340-6B-40-D010 / 340-EU6B-3040-9040-6LBW1LI-CC

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97	96	94	93
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91	89	87	85
3	101	95	89	85	99	93	88	84	90	86	83		88	85	82		86	83	80	79
4	96	88	82	78	94	87	81	77	85	80	76		83	79	75		81	77	74	73
5	91	82	76	71	89	81	75	71	79	74	70		78	73	70		76	72	69	68
6	86	77	71	66	85	76	70	66	74	69	65		73	68	65		72	68	64	63
7	82	72	66	61	80	71	65	61	70	65	61		69	64	61		68	63	60	59
8	78	68	62	57	76	67	61	57	66	61	57		65	60	57		64	60	56	55
9	74	64	58	54	73	63	58	54	62	57	53		62	57	53		61	56	53	52
10	70	60	54	50	69	60	54	50	59	54	50		58	53	50		58	53	50	49

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	297315
5°	242764
10°	177893
15°	153611
20°	131551
25°	121604
30°	98031
35°	63636
40°	48119
45°	26858
50°	15641
55°	10385
60°	7072
65°	4400
70°	3815
75°	2874
80°	2142
85°	2171



TEST NUMBER: P229177

CATALOG NUMBER: 340-6B-40-D010 / 340-EU6B-3040-9040-6LBW1LI-CC

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	320.5	12.2
10°-20°	636.4	24.3
20°-30°	752.4	28.7
30°-40°	526.5	20.1
40°-50°	245.7	9.4
50°-60°	85.2	3.3
60°-70°	32.4	1.2
70°-80°	13.2	0.5
80°-90°	3.1	0.1
90°-100°	2.0	0.1
100°-110°	1.2	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1709.3	65.3
0°-40°	2235.8	85.4
0°-60°	2566.7	98.1
0°-90°	2615.4	99.9
90°-120°	3.1	0.1
90°-150°	3.1	0.1
90°-180°	3.0	0.1
0°-180°	2617.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4557	
5°	3707	321
15°	2274	636
25°	1689	752
35°	799	527
45°	291	246
55°	91	85
65°	28	32
75°	11	13
85°	3	3
90°	0	0
95°	0	1
105°	0	1
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0



TEST NUMBER: P229177

CATALOG NUMBER: 340-6B-40-D010 / 340-EU6B-3040-9040-6LBW1LI-CC

CANDELA DISTRIBUTION (FULL):

0°	
0°	4557.2
2.5°	4331.8
5°	3706.9
7.5°	3090.5
10°	2685.3
12.5°	2445.6
15°	2274.3
17.5°	2120.2
20°	1894.8
22.5°	1726.4
25°	1689.3
27.5°	1546.7
30°	1301.3
32.5°	1024.5
35°	799.0
37.5°	653.5
40°	565.0
42.5°	439.5
45°	291.1
47.5°	202.6
50°	154.1
52.5°	117.0
55°	91.3
57.5°	71.3
60°	54.2
62.5°	40.0
65°	28.5
67.5°	25.7
70°	20.0
72.5°	17.1
75°	11.4
77.5°	8.6
80°	5.7
82.5°	2.9
85°	2.9
87.5°	2.9
90°	0.0
92.5°	0.0
95°	0.0
97.5°	2.9
100°	2.9
102.5°	2.9
105°	0.0
107.5°	0.0
110°	0.0



TEST NUMBER: P229177

CATALOG NUMBER: 340-6B-40-D010 / 340-EU6B-3040-9040-6LBW1LI-CC

CANDELA DISTRIBUTION (continued):

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)