

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: HALO COMMERCIAL

Report Number: P345275

Luminaire Tested: **PR4FS24D010 PR4M24MD8FSBZ 3000Lm3500K**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P345275  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1908-453-3)  
Test Lab: INNOVATION CENTER(G1)  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: HALO COMMERCIAL  
Catalog Number: PR4FS24D010 PR4M24MD8FSBZ 3000Lm3500K  
Description: PR4 MEDIUM LENS WITH, BRONZE FINISH  
Light Source: ARRAY OF HIGH LUMEN LEDs 80CRI / 3500K CCT  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 2281.5 lumens  
Efficiency: N/A  
Efficacy: 87.4 lumens/watt  
Spacing Criteria (0/90/45): 1/1/2001  
Luminous Opening: Circular (Dia: 0.4' x H: 0')  
CIE Type: Direct


Input Watts (W): 26.1  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P345275

CATALOG NUMBER: PR4FS24D010 PR4M24MD8FSBZ 3000Lm3500K

### Luminous Intensity Polar Plot





TEST NUMBER: P345275

CATALOG NUMBER: PR4FS24D010 PR4M24MD8FSBZ 3000Lm3500K

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	112	109	106	103	110	107	104	102	103	100	98		99	97	95		95	94	93	91
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88	86	83	82
3	98	91	85	80	96	89	84	79	86	82	78		84	80	76		81	78	75	73
4	92	83	76	71	90	82	76	71	79	74	70		77	73	69		75	71	68	66
5	86	76	69	64	85	75	69	64	73	68	63		72	67	63		70	66	62	60
6	81	70	63	58	79	70	63	58	68	62	58		66	61	57		65	60	57	55
7	76	65	58	53	75	65	58	53	63	57	53		62	57	52		61	56	52	51
8	72	61	54	49	70	60	53	49	59	53	49		58	52	48		57	52	48	47
9	68	57	50	45	67	56	50	45	55	49	45		54	49	45		53	48	45	43
10	64	53	46	42	63	53	46	42	52	46	42		51	45	42		50	45	41	40

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	151611
5°	150715
10°	148132
15°	143104
20°	135212
25°	123805
30°	108162
35°	87250
40°	64114
45°	47835
50°	36142
55°	28197
60°	22934
65°	17737
70°	12889
75°	6252
80°	1713
85°	1706



TEST NUMBER: P345275

CATALOG NUMBER: PR4FS24D010 PR4M24MD8FSBZ 3000Lm3500K

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	162.3	7.1
10°-20°	442.6	19.4
20°-30°	584.6	25.6
30°-40°	506.3	22.2
40°-50°	304.5	13.3
50°-60°	169.7	7.4
60°-70°	86.7	3.8
70°-80°	22.5	1.0
80°-90°	2.3	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1189.5	52.1
0°-40°	1695.8	74.3
0°-60°	2170.0	95.1
0°-90°	2281.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2281.5	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1733	
5°	1716	162
15°	1580	443
25°	1283	585
35°	817	506
45°	387	305
55°	185	170
65°	86	87
75°	18	22
85°	2	2
90°	0	



TEST NUMBER: P345275

CATALOG NUMBER: PR4FS24D010 PR4M24MD8FSBZ 3000Lm3500K

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	1733.3
2.5°	1728.3
5°	1716.5
7.5°	1696.3
10°	1667.8
12.5°	1627.4
15°	1580.3
17.5°	1521.5
20°	1452.6
22.5°	1371.9
25°	1282.8
27.5°	1180.2
30°	1070.9
32.5°	946.5
35°	817.1
37.5°	684.3
40°	561.5
42.5°	464.0
45°	386.7
47.5°	324.5
50°	265.6
52.5°	221.9
55°	184.9
57.5°	156.4
60°	131.1
62.5°	107.6
65°	85.7
67.5°	67.2
70°	50.4
72.5°	33.6
75°	18.5
77.5°	6.7
80°	3.4
82.5°	3.4
85°	1.7
87.5°	1.7
90°	0.0

(END OF REPORT)