

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P179770

Luminaire Tested: **LDA6A55935D010TE LARH40FL 6LAL1LI**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P179770  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P26680)  
Test Lab: INNOVATION CENTER-P2  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LDA6A55935D010TE LARH40FL 6LAL1LI  
Description: PORTFOLIO 6" Lensed Adjustable, Self-flanged, 40° Flood  
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 4403.0 lumens  
Efficiency: N/A  
Efficacy: 72.2 lumens/watt  
Spacing Criteria (0/90/45): 0.59 / 0.59 / 0.58  
Luminous Opening: Circular (Dia: 0.5' x H: 0')  
CIE Type: Direct


Input Watts (W): 61  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P179770

CATALOG NUMBER: LDA6A55935D010TE LARH40FL 6LAL1LI

### Luminous Intensity Polar Plot





TEST NUMBER: P179770

CATALOG NUMBER: LDA6A55935D010TE LARH40FL 6LAL1LI

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	115	112	110	108	112	110	108	107	106	105	103	103	101	100	99	98	98	96			96
2	110	107	103	101	108	105	102	99	102	99	97	99	97	95	96	95	93	92			92
3	106	101	97	94	105	100	96	94	98	95	92	95	93	91	93	91	89	88			88
4	103	97	92	89	101	96	92	89	94	90	88	92	89	87	90	88	86	84			84
5	99	93	88	85	98	92	87	84	90	86	84	88	85	83	87	84	82	81			81
6	96	89	84	81	94	88	84	80	87	83	80	85	82	79	84	81	79	78			78
7	92	85	80	77	91	85	80	77	83	79	77	82	79	76	81	78	76	75			75
8	89	82	77	74	88	81	77	74	80	76	74	79	76	73	79	75	73	72			72
9	86	79	74	71	85	78	74	71	78	74	71	77	73	71	76	73	70	69			69
10	83	76	71	68	83	76	71	68	75	71	68	74	71	68	74	70	68	67			67

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	707811
5°	552634
10°	484644
15°	442931
20°	323527
25°	157872
30°	38531
35°	8814
40°	1896
45°	861
50°	435
55°	650
60°	658
65°	558
70°	417
75°	360
80°	284
85°	0



TEST NUMBER: P179770

CATALOG NUMBER: LDA6A55935D010TE LARH40FL 6LAL1LI

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	930.4	21.1
10°-20°	2095.8	47.6
20°-30°	1234.6	28.0
30°-40°	120.5	2.7
40°-50°	9.6	0.2
50°-60°	5.5	0.1
60°-70°	4.2	0.1
70°-80°	2.0	0.0
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4260.8	96.8
0°-40°	4381.3	99.5
0°-60°	4396.4	99.8
0°-90°	4403.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4403.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	12912	
5°	10042	930
15°	7804	2096
25°	2610	1235
35°	132	120
45°	11	10
55°	7	5
65°	4	4
75°	2	2
85°	0	0
90°	0	



TEST NUMBER: P179770

CATALOG NUMBER: LDA6A55935D010TE LARH40FL 6LAL1LI

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	12911.5
2.5°	11556.5
5°	10042.5
7.5°	9286.7
10°	8706.3
12.5°	8284.0
15°	7804.4
17.5°	6960.6
20°	5545.7
22.5°	4000.1
25°	2610.0
27.5°	1557.6
30°	608.7
32.5°	318.9
35°	131.7
37.5°	43.6
40°	26.5
42.5°	17.1
45°	11.1
47.5°	6.8
50°	5.1
52.5°	6.0
55°	6.8
57.5°	6.0
60°	6.0
62.5°	5.1
65°	4.3
67.5°	3.4
70°	2.6
72.5°	2.6
75°	1.7
77.5°	1.7
80°	0.9
82.5°	0.9
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)